

“World class quality and reliability
at affordable prices.”

TW - 9202
TW - 9202Q

Dome Camera



This is the most popular dome camera, with very good reasons. Using a state-of-art Sony Super HAD CCD chipset, this dome will provide an extremely sharp picture, even in very low light, at an unbelievable price! A 3.6mm wide angle lens is for interior room applications. A convenient twist ring base mounting design leaves no exposed mounting screws or wires. The excellent video image produced by this camera with rival that of other cameras costing many times the price. This is definitely the dome of choice!



FEATURING

- High Resolution - 420 TVL
- 1/3" Sony Super HAD CCD
- Low Light - 0.5 Lux
- Auto Tracking White Balance
- Backlight Compensation
- 3.6mm Lens Standard
- Compact and Attractive Styling
- Tolerance up to max 18VDC



Dome Camera

SPECIFICATIONS

MODEL	TW-9202	TW-9202Q
Imaging Device	1/3"SONY Super HAD CCD	1/4"SONY Super HAD CCD
Signal System	PAL / NTSC	
Camera Pixels	PAL: 500(H) x 582(V) NTSC:510(H) x 492(V)	
Lens	3.6mm	
Sync System	Internal	
Back Light Compensation	Auto	
Scanning Mode	2:1 Interlaced	
Resolution	420 TV lines	
Minimum Illumination	0.5 lux @ F1.2	
Gain Control	Auto	
S/N Ratio	>48db(AGC OFF)	
White Balance	Auto Tracking White Balance	
Video Output	1.0 Vp-p75 ohm	
Power Source	DC 12V (tolerant max 18V)	
Working Temperature	-10°C to +60°C / 14°F to 140°F	

Note: Design and Specifications are subject to change without prior notice

Also available in Vandalproof Housing



Ceiling Mount AD01



Wall Mount AD03

Impact	Hi-impact reinforced polycarbonate Armor Dome withstand a blow 10-pound sledge hammer
Coating	Reinforced polycarbonate with special coating on surface.
Maximum Load	Maximum load 500 kg deformation without crack.
Die-Casing Base	Ultra hard grade aluminum with painted finish